2.4 mm RF Connector

The 2.4 mm connector is a type of RF (Radio Frequency) connector that is commonly used in high-frequency applications where a precise and reliable connection is required. It is similar to the 2.92 mm connector, but smaller in size.

The 2.4 mm connector has a screw-on coupling mechanism, which provides a secure and reliable connection. It also has a characteristic impedance of 50 ohms, making it suitable for high-frequency applications up to 50 GHz.



Part No	Part Name	Frequency
41-001	2.4 mm connector plug for 3506 cable	50 GHz



Part No	Part Name	Frequency
41-002	2.4 mm connector jack flange for 3506 cable	50 GHz



Part No	Part Name	Frequency
41-003	2.4 mm connector plug for RG405 cable	50 GHz



Part No	Part Name	Frequency
410-004	2.4 mm connector plug for 3507 cable	40 GHz

2.4 mm RF Connector



Part No	Part Name	Frequency
41-005	2.4 mm connector plug for 3507 cable	50 GHz




Part No	Part Name	Frequency
41-006	2.4 mm connector plug for zlb220 cable	50 GHz



Part No	Part Name	Frequency
41-007	2.4 mm connector plug for zlb360 cable	40 GHz



Part No	Part Name	Frequency
41-008	2.4 mm connector end launch solderless for PCB	50 GHz



Part No	Part Name	Frequency
41-009	2.4 mm connector 2-hole flange for pcb	50 GHz

2.4 mm RF Connector



Part No	Part Name	Frequency
41-010	2.4mm connector jack 2-hole flange	50 GHz



Part No	Part Name	Frequency
41-011	2.4mm connector jack 2-hole flange	50 GHz



Part No	Part Name	Frequency
41-012	2.4 mm connector 4-hole flange for pcb	50 GHz