


RevNo	Revision note	Date	Signature	Checked
V1.0	Sketch only	19/03/2026		

RoHS Compliant.



Interface Per: MIL-STD-348, IEC 60169-15

Material & Finishing:

1. Center conductor: Brass, Gold Plating
2. Insulators: PTFE
3. Body : Brass, Gold Plating

Electrical Data:

1. Impedance: 50 Ohms
2. Frequency: 0~3GHz
3. VSWR: ≤ 1.1 @ 900MHz,
 ≤ 1.15 @ 1800MHz,
 ≤ 1.25 @ 3000MHz,
 ≤ 1.35 @ 6000MHz,
4. Insertion loss: ≤ 0.05 dB @ 900MHz,
 ≤ 0.05 dB @ 1800MHz,
 ≤ 0.05 dB @ 3000MHz,
 ≤ 0.1 dB @ 6000MHz,
5. Dielectric Withstanding voltage: 1000V Min
6. Voltage Rating : 500V Max

Package : 1 PC per bag

Laser Mark: LenoRF

Label Content:

LenoRF
 Part No: 3.01.439
 Part Name: SMA JACK RA FLANGE MOUNTING JOINT (4HF)
 QTY: 1 PC
 Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g	
	Finish:	See Notes	Scale	8:1	
	Unit	mm	Page	01	
	REV.	V1.0	p/n	01	
Drawn	DATA:	Projection		DWG NO.	3.01.439
Checked	DATA:	Title:		Cust P/N.	TBD
Approved	DATA:	SMA JACK RA FLANGE MOUNTING JOINT (4HF)			