


A		B		C		D		E		F	
RevNo	Revision note	Date		Signature	Checked	RoHS Compliant.					
V1.0	Sketch only	01/07/2026									



Interface Per: MIL-STD-348,

Material & Finishing:

- 1. Center condutor: Brass, Gold Plating
- 2. Insulators: PTFE
- 3. Body : Brass, Ternary alloy Plating

Electrical Data:

- 1. Impedance: 50 Ohms
- 2. Frequency: 0~18GHz
- 3. VSWR: ≤1.3
- 4. Insertion loss: ≤0.2
- 5. Proof Voltage : 500 Veff
- 6. Working voltage: 350 Veff

Package : 1 PC per bag

Laser Mark: DX WAVE

Label Content:

DX WAVE
Part No: DX-3-17-179
Part Name: N PLUG TO N PLUG ADAPTOR
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01	DWG NO.	DX-3-17-179
Drawn		DATA:	Projection		Cust P/N.	TBD
Checked		DATA:	Title: N PLUG TO N PLUG ADAPTOR			
Approved		DATA:				