

RevNo	Revision note	Date	Signature	Checked
V1.0	Sketch only	21/10/2025		

RoHS Compliant.

Interface Per: MIL-STD-348
Cable Type: 086


Material & Finishing:

- Center conductor: Beryllium copper, Gold plating
- Insulators: PTFE
- Body: Beryllium copper,Gold plating
- Clasp: Beryllium copper,Gold plating

Electrical Data:

- Impedance: 50 Ohms
- Frequency: 0~6GHz
- VSWR: ≤1.1 @ 900MHz,
≤1.15 @ 1800MHz,
≤1.2 @ 3000MHz,
≤1.3 @ 6000MHz,
- Insertion loss: ≤0.05dB @ 900MHz,
≤0.05dB @ 1800MHz,
≤0.05dB @ 3000MHz,
≤0.1dB @ 6000MHz,
- Dielectric Withstanding voltage:1000V Min
- Voltage Rating : 500V Max

Package : 1 PC per bag
Laser Mark: LenoRF



Label Content:

LenoRF
Part No: 3.21.034
Part Name: SMP JACK FOR 086 CABLE
QTY: 1 PC
Date: WW/YY (Week/year)

Unless otherwise specified, tolerances as below: .x ±0.15 .xx ±0.1 .xxx ±0.05 Angle: ±2°	Material:	See Notes	Weight	g		
	Finish:	See Notes	Scale	8 : 1		
	Unit	mm	Page	01		
	REV.	V1.0	p/n	01		
	Drawn	DATA:	Projection		Cust P/N.	I BD
	Checked	DATA:	Title: SMP JACK FOR 086 CABLE			
	Approved	DATA:				